





## TGMC. Tuerca guía muelle corto



### > CARACTERÍSTICAS DE PRODUCTO

|          |                |
|----------|----------------|
| Material | Acero          |
| Acabado  | Electrozincado |



| Referencia | M   | B  | A  | t  | Diámetro muelle | Para carril       |
|------------|-----|----|----|----|-----------------|-------------------|
|            | mm  | mm | mm | mm | Ø               | mm                |
| TGM06C     | M06 | 19 | 35 | 6  | 18              | 21 x 41 / 41 x 41 |
| TGM08C     | M08 | 20 | 35 | 6  | 18              | 21 x 41 / 41 x 41 |
| TGM10C     | M10 | 20 | 35 | 8  | 18              | 21 x 41 / 41 x 41 |
| TGM12C     | M12 | 20 | 35 | 10 | 18              | 21 x 41 / 41 x 41 |

### > CARGAS ADMISIBLES

| Referencia | Métrica tornillo | F3 | F4  | T    |
|------------|------------------|----|-----|------|
|            | M                | kN | kN  | Nm   |
| TGM06C     | M06              | 5  | 1,0 | 3,5  |
| TGM08C     | M08              | 6  | 2,4 | 8,4  |
| TGM10C     | M10              | 7  | 3,5 | 17,0 |
| TGM12C     | M12              | 7  | 4,0 | 29,0 |